

# FLEXITALLIC L.P.

## Material Safety Data Sheet

No. FDP-009

REVISED: 13 July 2009

Contact Number 281-604-2400

### GENERAL INFORMATION

Manufacturer:

Flexitallic L.P.

6915 Highway 225

Deer Park, Texas 77536

Common Name, Trade Name, or Specification:

**Flexite Super Filled Spiral Wound Gasket**

DOT Hazard Code - N/A

### 1. HAZARDOUS INGREDIENTS AND EXPOSURE LIMITS

Although several of the ingredients used to formulate this product may be hazardous in the raw state, the manufacturing process results in a solid, infusible form, binding or otherwise rendering the mixture inert. We have identified below those hazardous constituents present in quantities greater than 1% (0.1% for carcinogens) that may be released from the product by overheating, burning, machining, abrading, or riveting.

Component	CAS Number	%	OSHA PEL	ACGIH TLV
Nickel	7440-02-0	<10	1 mg/m <sup>3</sup>	1 mg/m <sup>3</sup>
Chromium	7440-47-3	<15	0.5 mg/m <sup>3</sup>	0.5 mg/m <sup>3</sup>
Molybdenum	7439-98-7	<3	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Rubber	None	<10	N/A	N/A
Silica (Quartz)	14808-60-7	<5	0.1 mg/m <sup>3</sup> (respirable)	0.1 mg/m <sup>3</sup> (resp)
Graphite	7782-42-5	<35	2.5 mg/m <sup>3</sup> (respirable)	2.0 mg/m <sup>3</sup> (resp)
Acrylonitrile	107-13-1	<1	2 ppm	2 ppm
Butyl acrylate	141-32-2	<1	52 mg/m <sup>3</sup>	52 mg/m <sup>3</sup>

### 2. PHYSICAL AND CHEMICAL CHARACTERISTICS

Melting Point - None

Color - Dark Grey

Solubility in water - Insoluble

Specific Gravity -2.0 - 2.5

Odor -None

Form - Solid

### 3. FIRE AND EXPLOSION DATA

Auto-ignition Temperature: This product is inherently flame resistant.

Flammable Limits in Air: % in Air by Volume: LEL: N/A UEL: N/A

Extinguisher Media: Carbon dioxide, chemical, or foam

Special Firefighting Procedure: Material in or near fires should be cooled with a water spray or fog. A self-contained breathing apparatus, operating in the positive pressure mode, and full fire fighting protective clothing should be worn for combative fires.

Unusual Fire and Explosion Hazards: Thermal decomposition or combustion may produce dense smoke, oxides of carbon, and low molecular weight organic compounds whose composition has not been characterized.

### 4. PHYSICAL HAZARDS AND REACTIVITY DATA

Stability: Stable at normal temperatures and storage conditions

Incompatibility: None

Hazardous Decomposition Products: None

Hazardous Polymerization: Will not polymerize. This product is fully cured in the manufacturing process.

### 5. HEALTH HAZARDS

Carcinogenicity:	NTP Listed	IARC Listed	NIOSH Listed	OSHA Listed
Nickel	Yes	Yes*	Yes	No
Chromium	No	No	No	No
Molybdenum	No	No	No	No
Acrylonitrile	Yes	Yes**	Yes	Yes
Silica(Quartz)	Yes	Yes***	Yes	No
Butyl Acrylate	No	No	No	No
Graphite	No	No	No	No
Rubber	No	No	No	No

\* IARC classifies nickel as "carcinogenic to humans." Group 1

\*\* IARC classifies acrylonitrile as "probably carcinogenic to humans." Group 2A

\*\*\* IARC classifies quartz as "probably carcinogenic to humans." Group 2A

### Symptoms and Effects of Exposure to the Individual Components:

#### CHROMIUM

Inhalation hazards - Acute: exposure may result in cough and irritation of the respiratory system.

Chronic: Prolonged exposure may cause histologic fibrosis of the lungs.

Other hazards - Poisonous by ingestion; may cause severe gastrointestinal irritation.

## NICKEL

Inhalation hazards - Prolonged exposure may cause headache, vertigo, nausea, and vomiting, and may cause reproductive problems. IARC classifies nickel as "carcinogenic to humans." (Group 1)

Other hazards - Acute contact exposure may cause allergic contact dermatitis, pulmonary asthma, conjunctivitis, and inflammatory reactions around nickel-containing medical implants and prostheses.

Prolonged contact may cause substernal pain, cough, hyper-pnea, weakness, cyanosis, leukocytosis, pneumonitis, convulsions, and delirium. Ingestion may produce gastroenteric irritation resulting in vomiting, inflammation, and epigastric pain.

## MOLYBDENUM

Inhalation hazards - Dust may cause irritation of nasal and respiratory passages.

Other hazards - Molybdenum may be an eye irritant. Ingestion may cause diarrhea, loss of weight, liver and kidney damage.

## RUBBER (POWDERED)

Inhalation hazards - May cause mild irritation of respiratory tract. Repeated and prolonged inhalation of dust may lead to a benign pneumoconiosis. This condition may cause some lung function impairment but is reversible with reduced exposure.

Other hazards - Eyes - may cause mild transient eye irritation.

## SILICA DUST

Inhalation hazards - Acute: Exposure to silica dust may cause paroxysmal coughing, wheezing, dyspnea and upper respiratory tract irritation. Chronic: Prolonged exposure to silica dust may cause silicosis.

Quartz has been classified by IARC as "probably carcinogenic to humans." (Group 2A)

Other hazards - Eye or skin contact can cause temporary discomfort and irritation.

## GRAPHITE

Inhalation hazards - Acute: exposure may result in cough, dyspnea, black sputum, and fibrosis. Chronic: Prolonged exposure may cause pneumoconiosis. It is reported that diseases of the respiratory and cardiovascular system may be aggravated by exposure.

## ACRYLONITRILE

Inhalation Hazards - Exposure to acrylonitrile may cause somnolence, general anesthesia, cyanosis, and diarrhea. Symptoms include flushing of the face, salivation, irritation of the eyes and nose, photophobia, deepened respiration, nausea, weakness, and headache. IARC classifies acrylonitrile as "probably carcinogenic to humans." (Group 2A)

Other hazards - Acrylonitrile is a human systematic irritant and may be poisonous by skin absorption and ingestion. Target organs include the liver, central nervous system, brain, kidneys, and cardiovascular system.

## BUTYL ACRYLATE (BUTYL-2-PROPENOATE)

Inhalation hazards - Should be considered moderately toxic. May cause irritation of the nose and throat.

Other hazards - May cause dermatitis by contact, and can cause irritation of the eyes.

<b>6. FIRST AID</b>
---------------------

Inhalation: Move to fresh air. Obtain medical attention.

Eyes: Flush with water to remove particulate. Obtain medical attention.

Skin: Wash thoroughly with soap and water. If persistent irritation develops, obtain medical attention.

Ingestion: Obtain medical attention.

## 7. SPECIAL PRECAUTIONS AND SPILL / LEAK PROCEDURES

**Handling and Storage:** Shipping and storage may result in accumulation of dust in shipping containers. If this occurs, dispose of the container in an airtight polyethylene bag (see disposal instructions below) or remove dust by vacuuming or wet mopping. Vacuums used for this purpose should be equipped with HEPA filters. Do not use compressed air to blow dust from storage containers.

**Release or Spill :** If a release of dust occurs during machining, abrading, or riveting, remove dust by vacuuming or wet mopping. Vacuums used for this purpose should be equipped with HEPA filters. Do not use compressed air to blow dust from the workplace.

**Waste Disposal :** Disposal of solid waste is regulated by federal and state law. Waste should be placed in airtight containers, and disposed of properly. Contact local regulatory agency for guidance.

## 8. PERSONAL PROTECTION AND CONTROL

**Respiratory Protection :** Use NIOSH-approved respirator if exposure to dust, vapors, or fumes in concentrations exceeding PEL's or TLV's is possible. (See 29 CFR 1910.134 for respiratory protection standards)

**Ventilation :** Any operations which may produce dust, including machining, grinding, riveting, or abrading of this product, should be adequately exhausted to prevent inhalation of dust.

**Personal Protective Equipment :** Suitable respiratory protection should be worn if dust exposure is possible. All regulations and safe practices related to the use of respiratory protection must be observed. Refer to OSHA standards and NIOSH guidelines. If skin irritation occurs, gloves and other protective garments may be worn.

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date of revision. Flexitallic, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability, including direct, incidental or consequential damages for any reliance thereon.

This MSDS should not be used as a complete or accurate summary of the content of the product. For specific information on brand names, manufacturer's, or quantities, please refer to specific product specification documents where available.